REFERANCES

[1]. Römer, Kay, FriedemannMattern(2004), "The Design Space of Wireless Sensor Networks". *IEEE Wireless Communications* **11** (6):pp. 54-61.

[2]. F. Akyildiz, W. Su, Y. Sankarasubramaniam, and E. Cayirci(2002), "Wireless sensor networks: A survey," Computer Networks J., vol. 38, pp. 393-422.

[3]. J. Paek, K. Chintalapudi, J. Cafferey, R. Govindan, S. Masri(2005), A Wireless Sensor Network for Structural Health Monitoring: Performance and experience, In EmNetS.

[4] Q. Fang, J. Gao, and L. Guibas. Locating and bypassing holes in sensor networks.Mobile Networks and Applications, 11(2):187{200, 2006. ISSN 1383-469X. doi: 10.1007/s11036-006-4471-y. Cited on pages 92, 94, 95, and 98.

[5]. Muhammad Mostafa Monowar, Md. Obaidur Rahman, Al-Sakib Khan Pathan, and ChoongSeon Hong(2009), "Congestion Control Protocol for Wireless Sensor Networks Handling Prioritized Heterogeneous Traffic ".

[6] G. Feng, A. Agarwal, A. Jayaraman, and C. K. Siew.Modi_ed(2004), RED gateways underburstytra_c. IEEE Communications Letters, 8(5):323{325,ISSN 1089-7798.doi:10.1109/LCOMM.2004.827427. Cited on pages 59 and 62.

[7]. Amir Hossein Mohajerzadeh, Mohammad HossienYaghmaee(2010), "Tree Based Energy and Congestion Aware Routing Protocol for Wireless Sensor Networks " Scientific Research.

[8]. AvhadKalyani B(2012), "Congestion Control in Wireless Sensor Network-ASurvey" *IJCOT.*

[9] O. B. Akan and I. F. Akyildiz(2005), ESRT: Event-to-Sink Reliable Transport in WirelessSensor Networks. In IEEE/ACM Transaction on Networking (to appear).

[10] I. F. Akyildiz, W. Su, Y. Sankarasubramaniam, and E. Cayirci(2002), Wireless SensorNetworks: A Survey. Computer Networks, (Elsevier) Journal, 38:393{422.

[11] I. F. Akyildiz, M. C. Vuran, and O. B. Akan(2004), On Exploiting Spatial and TemporalCorrelation in Wireless Sensor Networks. In Proc. WiOpt'04: Modeling andOptimization in Mobile, Ad Hoc and Wireless Networks, pages 71{80.

[12] Raffaele B., Marco C., and Enrico G.(2001), Wireless Access to Internet via Bluetooth:Performance Evaluation of the edc Scheduling Algorithm. In WMI '01: Proceedingsof the first workshop on Wireless mobile internet, pages 43{49, New York, NY, USA. ACM Press.

[13] S. Baatz, M. Frank, C. K uhl, P. Martini, and C. Scholz(2002), Bluetooth Scatternets: AnEnhanced Adaptive Scheduling Scheme. pages 782{790, New York.

[14] S. Basagni, R. Bruno, and C. Petrioli(2003),Bluetooth Scatternet Formation in BluetoothNetworks. In Stefano Basagni, Marco Conti, Silvia Giordano, and Ivan Stojmenovic,editors, Ad Hoc Networking, New York, NY, IEEE Press.

[15] CC1000 Low Power FSK tranciever, Chipcon Corporation.

[16] CC2420 2.4 GHz IEEE 802.15.4/ZigBee-ready RF Transceiver.

[17] Jain, r. the art of computer systems performance analysis, first ed. wiley, 1991.

[18] MadWifi http://madwifi.org/.

[19] XBOW MICAz Mote Specifications, http://www.xbow.com/.

[20] ZigBee Alliance, IEEE 802.15.4, ZigBee standard, http://www.zigbee.org/.

[21] Radio Equipment and Systems (RES); High Performance Radio Local Area Network(HIPERLAN); Functional Specifications, ETSI, 1995.

[22] The impact of multihop wireless channel on tcp performance. IEEE Transactions onMobile Computing, 4(2):209–221, 2005. Student Member-Zhenghua Fu and

StudentMember-Haiyun Luo and Student Member-PetrosZerfos and Member-Songwu Lu andSenior Member-Lixia Zhang and Fellow-Mario Gerla.
[23]. Floyd, S., and Jacobson, V.(1993), “Random early detection gateways for congestion avoidance” IEEE/ACM Trans. Networking, 1(4), 397-413.
[24]. R. Szewczyk, A. Mainwaring, J. Polastre, D. Culler(2004), An Analysis of a Large Scale Habitat Monitoring, In Sensys.
[25]. I. F. Akyildiz, T. Melodia, and K. R. Chowdhury, “A survey on wireless multimedia sensor networks,” Computer Networks J., to appear.
[26]. Wang, B. Li, K. Sohraby and M. Daneshmand(2007), “Upstream Congestion control in wireless sensor networks through cross-layer optimization” ieee journal on selected areas in communications, vol. 25, no. 4.
[27]. S.Sridevi, M.Usha and G. Pauline AmerthaLithurin(2012)," Priority Based Congestion Control for Heterogeneous Traffic in Multipath Wireless Sensor Networks" inproc. IEEE conf.
[28]. A Comparative Study of Congestion Control Algorithms in IPv6 Wireless Sensor Networks Vasilis Michopoulos, Lin Guan, George Oikonomou, Iain Phillips Department of Computer Science Loughborough University Loughborough, UK LE11 3TU.
[29] R. Kapoor A. Capone and M. Gerla.E_cient(2002), Polling Scheme for Bluetooth Picocells.In In Proceedings of IEEE International Conference on Communications ICC 2001,volume 7, pages 1900{1994, Helisink, Finland.
[30] J. Beutel, O. Kasten, and M. Ringwald.BTnodes(2003) - A Distributed Platform forSensor Nodes. In Proc. 1st Intl. Conf. on EmbeddedNetworked Sensor Systems(SenSys), pages 292{293.
[31] G. Feng, F. Long, and Y. Zhang.Hop-by-hop congestion control for wireless meshnetworks with multi-channel MAC. In IEEE Global Telecommunications Conference,GLOBECOM, pages 1 {5, 2009. Cited on pages 127 and 130.
[32] P. Ferrie, P. Szor, R. Stanev, and R. Mouritzen(2004),Security responses: Symbos.cabir.Technical report, Symantec Corporation,.Cited on page 90.
[33] S. Floyd and V. Jacobson. Random early detection gateways for congestion avoidance(1993),IEEE/ACM Transactions on Networking, 1(4):397{413,ISSN 1063-6692.doi:10.1109/90.251892. Cited on pages 59 and 61.
[34] Y. Gao, J. Hou, and S. Paul(2003), RACCOOM- a rate-based congestion control approachfor multicast. IEEE Transactions on Computers, 52(12):1521 { 1534, ISSN0018-9340.Cited on page 55.
[35] V. Giruka and M. Singhal.Angular routing protocol for mobile ad hoc networks. In 25th
IEEE International Conference on Distributed Computing Systems Workshops, pages551{557, 2005. doi: 10.1109/ICDCSW.2005.42. Cited on pages 91 and 94.
[36] H. Goh, K. K. Tan, S. Huang, and C. de Silva(2006), Development of bluewave: A wirelessprotocol for industrial automation. IEEE Transactions on Industrial Informatics, 2(4):221 {230, ISSN 1551-3203. Cited on pages 4 and 20.
[37] V. Govindaswamy, G. Zaruba, and G. Balasekaran(2006), Receiver-window modified randomearly detection (RED-RWM) active queue management scheme: Modeling and analysis.In IEEE International Conference on Communications, ICC '06, volume 1, pages 158{163,doi: 10.1109/ICC.2006.254721. Cited on pages 59 and 62.